

## EDM 280

Environmental dust monitor for PM monitoring in ambient air

- Unique particle size range  $0.178 \mu\text{m} < D_o < 29.4 \mu\text{m}$
- Continuous real-time monitoring with high temporal resolution of PM values, total particle count (TC) and particle number size-distribution
- TÜV approved according to DIN EN 16450



## FEATURES

- Latest generation 19-inch based optical aerosol spectrometer, unique detection limit and excellent counting efficiency
- Touch display for intuitive menu control with color guided status information
- All-weather sampling system, -40 to 60 °C, 60 g/m<sup>3</sup> absolute humidity and wind
- Output of six dust mass fractions TSP, PM<sub>10</sub>, PM<sub>4</sub>, PM<sub>2.5</sub>, PM<sub>1</sub>, PM<sub>coarse</sub>, total particle concentration and particle number size distribution
- Aerodynamic aerosol focusing as per ISO 21501-1, no border zone error, total inlet flow analyzed in optical cell
- PSL traceable particle sizing as per ISO 21501-1
- Flexible data protocols: GRIMM protocol, Modbus, GESYTEC/Bayern-Hessen protocol

## BENEFITS

- Suitable for PM monitoring under any environmental conditions and at all sites (traffic, urban, background, maritime, mountain and others)
  - Approved immission measuring device for particulate matter PM<sub>10</sub> and PM<sub>2.5</sub> in air monitoring networks
  - Source apportionment with high time resolution for air pollution control strategies
  - Insensitive to vibrations, therefore also suitable for installation in measuring vehicles
- Robust design, energy efficient and lowest running costs
- Low maintenance due to internal particle-free purge-air circuit to protect the optical components
- Fits in all existing EDM (180, 180+) installations
- Stand-alone option with fully air-conditioned weather protection housing (construction site monitoring, port facilities, etc.)

## TECHNICAL DATA

<b>Detection principle</b>	Light scattering at single particles with diode laser; detection volume aerodynamically focused (ISO 21501-1), no border zone error
<b>Measured mass fractions</b>	TSP, PM <sub>10</sub> , PM <sub>4</sub> , PM <sub>2.5</sub> , PM <sub>1</sub> , PM <sub>coarse</sub>
<b>Particle size range</b>	0.178 µm < Do < 29.4 µm (Do = optical latex equivalent diameter)
<b>Size channels</b>	72, channel boundaries equidistant, 32 channels per decade
<b>Mass concentration</b>	0 ... 12,000 µg/m <sup>3</sup> for PM <sub>10</sub> 0 ... 5,100 µg/m <sup>3</sup> for PM <sub>2.5</sub> (with 10 % coincidence error for Arizona Dust A1 ultrafine)
<b>Detection limit</b>	0.1 µg/m <sup>3</sup> for PM <sub>10</sub>
<b>Zero level</b>	≤ 0.1 µg/m <sup>3</sup>
<b>Sample volume flow</b>	1.2 l/min, accuracy ≤ ±2 %, constant at the orifice plate by regulation
<b>Internal purge air</b>	0.3 to 0.5 l/min, protection of laser optics, reference air for self-test
<b>Storage interval</b>	Selectable, 6 seconds, 1, 5, 10, 15, 30, 60 minutes, daily average value
<b>Data interfaces</b>	RS-232 (selectable up to 115,200 baud/s), USB-B, Ethernet, USB flash drive (USB 2.0), data logger
<b>Data protocol (ASCII)</b>	GRIMM protocol, Modbus TCP, GESYTEC/Bayern/Hessen Protocol

## OPTIONAL ACCESSORIES

- 199 Stand-alone, fully air-conditioned weather protection housing, providing space for EDM 280 and other 19" rack instruments

<b>Meteo sensor</b>	<ul style="list-style-type: none"> <li>• Temperature: -50 ... 60 °C, ±0.2 °C (-20 ... 50 °C), otherwise ±0.5 °C (&gt; -30 °C)</li> <li>• Relative humidity: 0 ... 100 % RH, ±2 % RH</li> <li>• Air pressure: 300 ... 1200 hPa, ±0.5 hPa (0 ... 40 °C)</li> </ul>
<b>Operation</b>	Via touch display or PC via data interface
<b>Power supply</b>	Wide range power supply 100 ... 240 VAC at 50 ... 60 Hz, 4 A
<b>Power consumption</b>	<ul style="list-style-type: none"> <li>• Typical 25 W (continental warm)</li> <li>• Typical 40 W (tropical humid)</li> <li>• Typical 80 W (polar cold)</li> <li>• Typical 220 W (maximum equipment, all heaters at maximum power)</li> </ul>
<b>Conditions (sample air on site)</b>	<ul style="list-style-type: none"> <li>• Temperature: -40 ... 60 °C</li> <li>• Relative humidity: 100 % (-40 °C) ... 30 % (60 °C) or maximum 60 g/m<sup>3</sup> absolute humidity</li> <li>• Ambient pressure: 530 ... 1,080 hPa</li> </ul>
<b>Conditions (measuring container)</b>	<ul style="list-style-type: none"> <li>• Temperature: 5 ... 40 °C</li> <li>• Relative humidity: 5 ... 90 %, non-condensing</li> </ul>
<b>Transport and storage</b>	-20 ... +50 °C, RH < 95 % (non-condensing)
<b>Dimensions (H x W x D)</b>	<ul style="list-style-type: none"> <li>• 19" spectrometer: 180.5 x 434 x 320 mm</li> <li>• Sample tube holder: 88.9 x 441 x 156 mm</li> <li>• Sample tube with sampling head: 1500 (L) x Ø 45 (tube)/Ø 105 mm (Sigma-2 sample inlet)</li> </ul>
<b>Weight</b>	<ul style="list-style-type: none"> <li>• Total: 20.5 kg (with meteo sensor 157 L, 2.35 kg)</li> <li>• 19" spectrometer: 10.45 kg</li> <li>• Sample tube holder: 2.4 kg</li> <li>• Sample tube with sampling head: 5.3 kg</li> </ul>



**Enviro**  
Technology Services Ltd  
part of CuraTerra

## UK & Ireland Distributor

Kingfisher Business Park, London Road, Stroud, Gloucestershire, GL5 2BY, UK

**Tel: +44 (0) 1453 733200    sales@et.co.uk    www.et.co.uk**