



## The Model T100 UV Fluorescence SO<sub>2</sub> Analyzer



The Model T100  $SO_2$  analyzer uses the proven UV fluorescence principle and advanced electronics to allow accurate, dependable, continuous measurements for ambient air quality, stack gas monitoring and other applications.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- All other T Series instrument platform features
- Lifetime technical support by phone and email
- Standard two-year warranty

## T100 Specifications

Ranges	Min: 0 - 50 ppb full scale Max: 0 - 20,000 ppb full scale (selectable, dual-range supported)
Measurement Units	ppb, ppm, μg/m³, mg/m³ (selectable)
Zero Noise	< 0.2 ppb (RMS)
Span Noise	< 0.5% of reading (RMS) above 50 ppb
Lower Detectable Limit	< 0.4 ppb
Zero Drift	< 0.5 ppb/24 hours
Span Drift	< 0.5% of full scale/24 hours
Response Time	< 120 seconds to 95%
Linearity	1% of full scale
Precision	0.5% of reading above 50 ppb
Sample Flow Rate	650 cc/min ±10%
Power Requirements	100V-120V, 220V-240V, 50/60 Hz
Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
Recorder Offset	±10%
Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
Optional I/O	1 x USB com port 1 x RS485 4 x digital alarm outputs Multidrop RS232 3 x 4 - 20mA current outputs
Operating Temperature Range	5 - 40°C (with US EPA Approval)
Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
Weight	35.7 lbs (16.2 kg)
Certifications	US EPA: EQSA-0495-100 EU: EN14212 TÜV Rheinland QAL1 Certified: EN15267 MCERTS: Sira MC 050067/08 CNEMC: 质(认)字 No. 2018-209 Report

Specifications subject to change without notice. All specifications are based on constant conditions.



## **UK & Ireland Distributor**