

# ES-405 Simultaneous Particulate Profiler

**The ES-405 is a near reference air quality sensor designed to provide accurate real-time measurements of PM10, PM4, PM2.5, and PM1 particulate concentrations simultaneously.**

It reports these four key particulate concentrations in both indoor and outdoor environments. The rugged weatherproof enclosure allows use in the harshest environments for reliable continuous outdoor operation, and the inlet heater reduces moisture related measurement error. The sensor incorporates sheath air to prevent particles from contaminating the internal optics of the sensor. The ES-405 can be wall-mounted or installed on a vertical mast.

All ES-405 Particulate Profilers are manufactured at an ISO-9001 facility. Calibrations are performed to NIST traceable standards.

Data output can be configured as fast as each minute or with longer averaging intervals. Send data directly to the cloud for remote download and analysis with a CCS Modem 2 accessory. External meteorological sensors can be connected to the unit.

## APPLICATIONS

- Air Quality Surveillance
- Rapid Source Apportionment Determination
- Emergency Responder Applications
- Near-Roadside Monitoring
- Particulate Emission Studies
- Environmental Clean Up Sites
- Obtain Localized Particulate Data for Community Health & Policy





## STANDARD ACCESSORIES

- Weatherproof TSP Inlet with Debris Screen
- External Power Cable
- Mounting Bracket
- USB Cable

**Ask About the AQ EAGLE System:  
A Preconfigured Air Monitoring  
Solution utilising the ES-405!**

## OPTIONAL ACCESSORIES

- Alarm Contact Closure Can be
- Used to Signal an External Warning Light, Logic Controller, or Logger Input to Take Action
- CCS Comet Cloud Modem
- AIO 2 Sonic Weather Sensor
- MSO Weather Sensor
- 10' Aluminum Tripod
- RS232 Communication Cable
- RS485 Communication Cable



# Product specifications

<b>Model Number</b>	ES-405
<b>Operation</b>	Right angle light scatter detection, using a laser diode as light source.
<b>Measurement Resolution</b>	0.1 µg/m <sup>3</sup>
<b>Number of Mass Channels</b>	4 (PM1, PM2.5, PM4, PM10)
<b>Data Storage Intervals</b>	1, 5, 10, 15, 30, or 60 minutes
<b>Sample Air Flow Rate</b>	1.0 LPM
<b>Sheath Air Flow Rate</b>	1.0 LPM
<b>Flow Control</b>	Active volumetric flow control
<b>Communications Connections</b>	RS-485, RS-232, USB, Optional CCS Modem
<b>Operating Temperature</b>	0° to +50° C
<b>Storage Temperature</b>	-20° to +60° C
<b>Ambient Humidity Range</b>	0 to 95%, non-condensing
<b>User Interface</b>	Menu-driven interface with 4x20 character OLED display and dynamic keypad.
<b>Power Supply</b>	Universal 100-240 VAC input, 50/60Hz.
<b>Power Consumption</b>	12 VDC. Max operating current 1300mA.
<b>Alarm Contact Closure</b>	Normally open/ normally closed contact closure relay output. Contact rating 1.0A @ 30V DC max.
<b>Weight</b>	
<b>Dimensions</b>	8.5 lbs without power supply, 10 lbs with power supply. Height: 20" Width: 8" Depth: 6"
<b>Communications Protocol</b>	Terminal Command Set, Modbus 7500 Protocol

*Specifications are subject to change at any time.*

## Office Location

Kingfisher Business Park  
London Road  
Stroud  
Gloucestershire  
GL5 2BY

Registered in England No. 01726773